

Welding Machine



JK-6200

Specification

Total power	5KW	Heating tube power	4KW	Upper wheel pressure	0.15MPa	Width of the pinch wheel	25.4mm
Rated voltage	220V	Maximum temperature	700°C	Air blower power	370W	Diameter of pinch wheel	65mm
Rated frequency	50HZ	Air pressure	0.35—0.5MPa	Lifting travel of up wheel	18mm—30mm	Width of air gun nozzle	22mm

Hot-air seam sealing machine is mainly used for seam sealing. It is a glue reinforcement process. The adhesive tape at the seam is heated by the machine, and the pressure roller is continuously rotated to feed and pressurize, and the tape is closely adhered to the fabric, to prevent water, bacteria, viruses, air, etc. from intruding into the inner side through the seam to achieve protection. It is widely used for products such as medical protective clothing, waterproof shoes, diving suits, sports suits, mountaineering suits, waterproof bags, raincoats, tents and awnings etc.



medical protective clothing




waterproof shoes



mountaineering suits




diving suits



bathing suits



- 1 Delta PLC control system, precise temperature control, temperature fluctuation is only $\pm 1^{\circ}\text{C}$, which can ensure the bonding quality.



- 2 Fully automatic tape feeding, tape cutting, compensation and micro back, which can reduce waste and increase productivity.



- 3 High-quality heating tubes, uniform heating, stable wind output is used to greatly extend service life.



- 4 Touch-type multi-function display screen, easy setting and simple operation which can be freely programmed according to user needs.